



CREATE A LASTING IMPRESSION

## PS Pro Cast Laminate Matte

- UV protection added to vinyl
- For vehicle wraps and graphics
- 1.2 mil optimizes flexibility and conformability
- ASTM E-84 Class A Flammability Rating

### Construction

Product Number:	LG L02 LAM2979 60150M
Adhesive:	Clear Permanent Acrylic
Film:	1.2 mil Premium Clear Cast Vinyl
Liner:	50 lb glassine
Gloss Level:	>10 (avg.) @ 60°

### Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Outdoor - up to 5 years vertical exposure	
Minimum Application Temperature:	+ 50° F (Minimum for Substrate)	
Service Temperature Range:	-50° F to 225° F	
Dimensional Stability:	0.01 in. (48 hrs. @ 150° F)	
Elongation	120%	
Chemical Resistance:	Resistant to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvent and salts	
Typical Adhesion Values:	180° Peel Test	
	Substrate	24 hrs.
	Stainless Steel	3.0 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity.	



961 Stockton Avenue, San Jose, CA 95110  
P: (800) 250-4252 | F: (408) 294-2045 |  
[www.sgpweb.com](http://www.sgpweb.com)