

Technical Data Sheet

SuperSmooth™ PET GreyBack

SuperSmooth PET GreyBack is a non-curling banner with a grey back and supersmooth print surface, which makes it ideal for high resolution printing. The grey back-side prevents light transparency and shadowing making SuperSmooth PET GreyBack ideal for pop-up, roll-up, X displays, and an array of other close viewing, indoor applications. SuperSmooth PET GreyBack does not require lamination and is available in matte finish from 38" - 126" wide.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH	
Support Cloth	DIN ISO 2076	Polyethylene terephthalate		
Yard dtex	DIN EN ISO 2060	N/A	N/A	
Total Weight	DIN EN ISO 2286-2	450 g/m ²	13 oz/yd²	
Tensile Strength	GB/T10403-2006	1288 x 1492 N/5cm	147.08 x 170.38lbs/inch	
Tear Strength (warp/weft)	HG/T2581-1994	3.6 x 3.5 N/5cm	0.41 x0.39 lbs/inch	
Fire Resistance	NFPA701			

Applications

	Pop-Up Displays	Banner	Roll-Up Displays	Blockout	Scrolling Signs	X-Displays	Trade Show Displays
Applications							

Ink Printability

S	Solvent	Eco Solvent	UV	Latex	Screen Printing	Dye Transfer	Dye Direct

Available Sizes

Metric (m)	English (inches)
0.96, 1.37, 1.60,	38", 54", 63", 80",
2.0, 3.20	126"

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

