



www.sgpweb.com 1.800.250.4252 orders@sgpweb.com





- Coated on both sides with a pressure sensitive, permanent solvent acrylic adhesive, both protected by a clear PET release liner
- UV stability for graphic prints



- Recommended for second surface mounting (face mounting) of images to clear substrates such as PETG, acrylic, plexiglass or glass
- Ideal for lenticular imaging applications, backlit displays touch screens, high quality photos
- Suitable for indoor and short-term outdoor use

Product Structure

- Release liner: Siliconized 1 side PET
- Adhesive: Permanent solvent acrylic (pressure sensitive)
- Film: Clear PET

Product Characteristic

- Film thickness: 0.5 mil (12.7 μ), 2.8 mil/71 μ
- Adhesive layer: 0.9 mil (23µ)
- Film/adhesive ratio: 0.9:1:0.9
- UV protection factor: UV stable
- Outdoor durability: 2 years
- Peel strength (20 min, F1M1): 12.8 N/25mm (glass 24 hrs)
- Service temperature range: -40°F to 212°F (-40°C to 100°C)
- Shelf life: 2 years
- Storage conditions: 59°F to 72°F (15°C to 22°C);
 50-55% relative humidity

Process Setting

- Roller laminator: Room temperature 104°F (40°C);
 Speed: 1 ft to 8ft (0.3m to 2.5m) per minute
- Press: Not recommended

Available Sizes

• 51"x200'

Part Number

• LG A01 ADH271651200C



scan for more info