

## Platinum LTR Cling

### ***Product Overview:***

Platinum LTR cling is a vinyl film with a low-tack pressure sensitive adhesive for use on smooth surfaces. It is available in white or clear, polished or matte surface.

### ***Properties:***

Can be applied to most clean, non-porous surfaces

Withstands many weather conditions

Temperature ranges from -40 F to 200 F

### ***Applications:***

Interior and exterior doorway signs

Refrigerator/ freezer point-of-purchase signs

Point-of-purchase decals for appliances

Window decals for stores and cars, etc.

### ***Technical Data Properties:***

Thickness (mil): 4.8 to 5.2 mil with adhesive

Printing: Material suitable for screen process, offset lithography, and flexography

Dimensional stability: Good

Min. Application Temperature: +40 F

Exterior Exposure: Test for UV discolor under extreme conditions

Adhesion: Glass- 8 oz. to 16 oz. / in. Removable up to 1 year on interior applications and 6 months on exterior applications.

Water and Humidity Resistance: Fair. Slight haze will develop in high humidity conditions and will clear when normal humidity returns.

Storage Stability: 6 months when stored at 70 F and 50 % relative humidity.

Note: The stated values are typical data and are not specification of guarantee. SGP suggests that the purchaser confirm product compatibility prior to use of this product. Stated values are believed to be accurate, but all information is presented without guarantee or responsibility on the part of SGP.