

ViziPrint®

Deco +

This optically clear printable window film utilizes a special ink-receptive top coat for greater adhesion of inks. ViziPrint® Deco + is ideal for architectural applications where decorative glass details are needed to create dynamic spaces, including conference rooms or private meeting areas. It can also be used to create graphics and window decals for retail storefronts and POP or backlit displays.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS
- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

2 mil
Clear
Transparent
PET



CREATE ARCHITECTURAL APPLICATIONS

3 6 0

EXHIBITIONS

APPLICATIONS

Smooth Flat Surfaces
Retail Backlit Displays
Window Graphics
Decals & Stickers

Certified for
HP Latex Inks

This media may not be certified for all HP Latex ink and printing systems. Please check the HP media locator website at hp.com/go/mediasolutionslocator



SONOMA
GRAPHIC
PRODUCTS
www.sgpweb.com

ViziPrint®

Deco +

ViziPrint® Deco + is a 50µ (2 mil) optically clear gloss PET film, coated with a permanent clear acrylic adhesive and protected by an opaque siliconised PET release liner that has a super smooth profile to enhance the clarity when applied to glass. It has a special top coat to enhance the adhesion of inks. The film's high quality adhesive adheres to most substrates.

- IDEAL FOR HIGH QUALITY GRAPHICS FOR HIGH END RETAIL STOREFRONTS

- SUITABLE FOR CONFERENCE ROOMS AND ARCHITECTURAL APPLICATIONS.

INSTALLATION RECOMMENDATION

The surface must be clean and smooth and free of defects before application. Use gloves to avoid fingerprints. Wet installation is recommended.

TECHNICAL SPECIFICATION

PRODUCT STRUCTURE

Film	Scratch-Resistant Gloss Transparent PET with Ink-Receptive Top Coat
Adhesive	Clear Permanent Acrylic (Pressure Sensitive)
Release Liner	Siliconised 1 Side PET

PRODUCT CHARACTERISTIC

Film Thickness	2 mil (50µ) 2.8 mil (70µ)
Adhesive Layer	0.8mil (20µ) (70µ)
Film/Adhesive Ratio	2:0.8
Outdoor Durability	3 Years
Fire Rating	Class B1 (DIN 4102-1)
Application Temperature	>41°F (5°C)
Service Temperature Range	-4°F to 266°F (-20°C to 130°C)
Shelf Life	2 years
Storage Conditions	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity

SONOMA
GRAPHIC
PRODUCTS
www.sgpweb.com

For more info, contact your local SGP sales rep:

Northern CA

Doug King, 408.701.7202

Southern CA

Dereck Cruz, 626. 201.8932

Central CA/Southern CA/Hawaii

Sommer Della Bitta, 916.947.2602

Washington & Oregon

Chuck Vandervort, 206.235.4191

Pam Pare, 503.317.6759