

AQUEOUS

Legacy Aqueous Backlit Film

Excellent Printing Compatibility For Latex

Legacy Aqueous backlit film is for use with dye and pigment inks. This 9mil/270g PET Film has a smooth matte, ultra white finish to provide consistent ink absorption. The brilliant print quality will stand out when with or without light. It is ideal for backlit signage applications, and produces vivid color and high resolution images.

APPLICATION

light box advertising, illuminated displays, trade show and exhibition graphics, signage

Special Backlit application

- Cosmetics
- Fashion image
- Air Port & great image application

SPECIFICATION

Caliper	215 micron (8.6 mil)
weight	270g
Base material	PET
Surface	Matte
Width	36", 50", 60"
Length	30m (100 ft)
Core	2"

COMPATIBILITY

(★ Excellent, ◎ Very good, ○ Good, △ Fair, X Not good)

Ink Compatibility

Dye	Pigment	LATEX
◎	★	★

Printer Compatibility

HP				EPSON			CANON
LATEX	Dye	UV	Z-series	Dye	Ultra	K3	IPF
★	◎	★	★	◎	★	★	★

TECHNICAL DATA

Caliper	215 micron	ASTM D645
Gloss	60° : 3.0 ≥ / 85° : 5.0 ≥	ASTM D2457
L.a.b	85 / 1.0 / -6.0	ANSI T (D50/2°/Abs/No)

GUIDELINES

Printing Tip

Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 30~60%
Use care in handling printed material, surface susceptible to abrasion
To optimize the printing quality, printer need to be set for highest print quality.

Lamination:

Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.

Storage:

It is recommended to store in the closed original packing in a cool and dry environment
Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH

Shelf Life:

One year stored in original package in recommended condition

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.