

# Adhesive Backed 5 mil Gloss White Film

## Clear Ultra Removable Adhesive, 90# Lay Flat Liner

### for Solvent, Latex & UV Printers

- For applications that require easy removability from smooth surfaces such as painted drywall
- Print to edge - no border needed around printed graphics
- Compatible with OEM Solvent, Latex & UV Curable Inks - 24 hour cure time recommended before cutting

#### Construction

Product Number:	KC SOL/WALLGRAPIX
Adhesive:	Low Peel Removable Acrylic
Film:	5 mil Semi Rigid Film
Liner:	90# Lay Flat
Finish:	Gloss White
Gloss Level:	62(avg.) @ 60°

#### Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability:	Recommended for indoor use. Removable up to one year under normal interior conditions. Please test first for outdoor applications.	
Minimum Application Temperature:	+50° F (Minimum for Substrate)	
Service Temperature Range:	-40° F to +180° F	
Chemical Resistance:	Resistant to distilled water and detergent. Poor resistance to alkalis, mild acids, most petroleum based oil, grease and aliphatic solvents and salts.	
Typical Adhesion Values:	180° Peel Test	
	<u>Substrate</u>	<u>24 hrs.</u>
	Stainless Steel	1.5 lb/in
Shelf Life:	1 year from ship date when stored in proper conditions 70° F and 50% relative humidity.	

