

## PS Pro Calendered Laminate Gloss

- UV protection added to vinyl
- Suitable for indoor and outdoor applications

### Construction

|                 |                              |
|-----------------|------------------------------|
| Product Number: | LG L02 LAM287X XX150G        |
| Adhesive:       | Clear Permanent Acrylic      |
| Film:           | 3 mil PVC (with UV absorber) |
| Liner:          | 4.6 mil (78# C1S Liner)      |
| Gloss Level:    | 85 (avg.) @ 60°              |

### Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

|                                  |  |                |
|----------------------------------|--|----------------|
| Durability:                      | Outdoor - up to 3 years  |                |
| Minimum Application Temperature: | + 40° F (Minimum for Substrate)  |                |
| Service Temperature Range:       | -40° F to +180° F (-46° C to + 82° C)  |                |
| Temperature Resistance:          | -65° F to + 225° F   |                |
| Chemical Resistance:             | Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvent and salts. |                |
| Typical Adhesion Values:         | 180° Peel Test   |                |
|                                  | <u>Substrate</u>   | <u>24 hrs.</u> |
|                                  | Stainless Steel  | 3.0 lb/in      |
| Shelf Life:                      | 1 year from ship date when stored in proper conditions 70° F and 50% relative humidity               |                |