



2227 Capricorn Way, Ste. 203
Santa Rosa, CA 95407
1.800.250.4252

PSA White 3mil Vinyl Air Release, Gray Permanent Adhesive

Can be used for interior and exterior signage

Uses include outdoor signage, promotional and point of purchase graphics, trade show displays

Compatible with OEM Solvent and Mild Solvent Ink

Construction

Adhesive: Gray Permanent Acrylic

Film: 3 mil Vinyl

Liner: 6.4 mil (88# Layflat Liner)

Finish: Gloss & Matte White

Gloss Level: + 70 (avg.) @ 60°

Typical Performance Values

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

Durability: Outdoor - up to 3 years

Minimum Application Temperature: + 40° F (Minimum for Substrate)

Service Temperature Range: -40° F to +180° F (-46° C to + 82° C)

Temperature Resistance: -65° F to + 225° F

Chemical Resistance: Resistant to alkalies, mild acids, most petroleum based oil, grease and aliphatic solvent and salts.

Typical Adhesion Values: Test Stainless Steel Typical Average

Peel 24 hour 3.0 lbs. PSTC-101

Tack 1.4 lbs. PSTC-16

Dimensional Stability: Strinkage MD less than 0.5%

CD less than 0.6%

Surface Tension: 35 + dynes

Shelf Life: 1 year from ship date when stored in proper conditions

70° F and 50% relative humidity