

SpotOn™ Matte

Print Media

SpotOn™ Matte is a 4 mil (100μ) printable matte monomeric PVC film with a dot patterned, pressure sensitive polyacrylate adhesive. The adhesive is protected by a single-sided, siliconized clay coated Kraft release liner. This high quality, ink receptive printable vinyl was specifically developed for easy, bubble-free application of vibrant graphics to a wide range of substrates. SpotOn™ Matte is available in clear frosted and white versions.

Typical Applications

- Ideal for short-term indoor wall and window applications.
- Graphics for advertising as well as other promotional applications.
- Excellent for applications where easy, tool-free installation is necessary.

Print Compatibility

- (Eco) Solvent
- Latex
- UV

Product Structure

Film	Matte Monomeric PVC	4.5 mil (113μ)
Adhesive	Dot Pattern Polyacrylate	
Release Liner	135 gsm Siliconized 1 Side Bleached Clay Coated Kraft	

Physical Characteristics

Finish and Color	Matte Clear Frosted	Matte White
Film Thickness	4 mil (100μ)	4 mil (100μ)
Adhesive Layer	0.5 mil (13μ)	0.5 mil (13μ)
Film/Adhesive Ratio	4:0.5	4:0.5
UV Protection Factor	Not Applicable	Not Applicable
Outdoor Durability	Not Applicable	Short-Term
Application Temperature	>41°F (5°C)	>41°F (5°C)
Service Temperature Range	-4°F to 149°F (-20°C to 65°C)	-4°F to 149°F (-20°C to 65°C)
Flame Retardancy	Self Extinguishing (internal test)	Self Extinguishing (internal test)
Shelf Life	1 year	1 year

Storage Conditions	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity	64°F to 77°F (18°C to 25°C); 40 - 65% Relative Humidity
--------------------	---	---

Installation Recommendations

Please see SpotOn™ installation instructions for further details. The surface must be clean and smooth and free of defects before application.

IMPORTANT NOTE:

Information is intended only as a guide and is given without guarantees. Purchasers should independently determine, prior to use, the suitability of each material for their specific purpose. Follow the indications on the package, ask for the safety data sheets and always follow the indications contained therein.

Only the correct use of the product will allow satisfactory results. For this reason, Drytac is not responsible for improper use of the product, either by application or substrate applied to. Make certain that product is right for the desired use, and work according to the instructions given in our technical data sheets. If in doubt of the appropriate application methods or use, contact Drytac at one of the phone numbers listed below.